18/20/1/10/2011

OF MORATUWA, SRI LANK.

DEVELOPMENT OF HOLONOMIC MOBILE PLATFORM FOR FIELD ROBOTIC **APPLICATIONS**

A Thesis submitted to the Department of Electronics and Telecommunications Engineering University of Moratuwa in partial fulfilment of the requirements for the degree of Master of Philosophy



W.R. De Silva

Supervised by: Dr Rohan Munasinghe

Department of Electronics and Telecommunications Engineering University of Moratuwa, Sri Lanka

March 2011

University of Moratuwa



100855



DECLARATION

The work submitted in this thesis is the result of my own investigation, expect otherwise stated.

It has not already been accepted for any degree, and is not been concurrently submitted for any other degree.

UOM Verified Signature

W. R. De Silva

Date: 10 March 2011

We/I endorse the declaration by the candidate.

UOM Verified Signature

Dr Rohan Munasingha

Dr. Rohan Munasinghe
Senior Lecturer
Dept. of Electronic and
Telecommunication Engineering
University of Moratuwa.

Abstract

Most mobile platforms or vehicles used today are non holonomic. They only have one or two independent degrees of freedom. Due to that its maneuverability is limited and often requires much space to control functions like turning and parking. By improving degrees of freedom (improving the maneuverability) of a vehicle, it can follow many complex trajectories that are difficult or impossible by conventional non holonomic vehicles. Any mobile platform that has three independent degrees of freedom in a plane is a holonomic platform. Independent degrees of freedom means that it can change its orientation or position without effecting other motions unlike in car type vehicles that require turning or changing its orientation when need to move. Holonomic motion is very useful to acquire abilities such as, avoid any obstacle while keeping its orientation the same, capability to move in constrained spaces and track a target while moving in an arbitrary trajectories etc. Because of these advantages and capabilities some of the scientific and industrial researches are targeting to develop holonomic mobile platforms. Already robotics community have managed to build some working models and used in applications like robot soccer games and mobile robot manipulators. Many different mechanisms have been created to achieve the holonomic capability. These include various arrangements of Swedish wheels or omni wheels, chains of spherical or cylindrical wheels, ball wheels and powered caster wheels etc. While most of these designs are practical in indoor environments they are not suitable for outdoor operations in large scale versions. In this research project our goal was to develop a viable design to achieve holonomic capability that minimizes these problems and more suited to outdoor operations. The proposed design has a wheel arrangement similar to a car but with the capability of independent driving and steering capability of each of the four wheels. Car type rolling and steering mechanism avoid any uneven

wear of the wheels and avoid lateral forces applied on the wheels. Wheel driving and steering mechanism was designed such a way that wheels can be steered 360 degrees continuously without interfering with the wheel drive system. This enables the platform to move in complex trajectories continuously without stopping for wheel resetting. The developed platform has increased ground clearance that is necessary for outdoor rough terrain operations like farming. Although these benefits exist, controlling the robot to acquire the desired motion is very complex and need innovative algorithm. Four independent wheels with eight degrees of freedoms to achieve three degree of freedom motion is a redundant control problem and require complex control system. Using inverse kinematics model of the platform and multiprocessor design with advance micro-controllers we have tried to solve these issues and were able to achieve successful performance.



Dedicated to my parents Sujatha and Dayawansha
University of Moratuwa, Sri Lanka.

Electronic Theses & Dissertations
to my loving wife Nalika
www.lib.mrt.ac.lk

Acknowledgments

I would like to take this opportunity to convey my sincere thanks to Dr Rohan Munasingha, my research supervisor in suggesting such a research project that invoked my design abilities. It has benefited immensely from his valuable advices, suggestions to fruitful the outcomes of the project. I also thank to Dr Palitha Dassanayake and senior lecturer Mr. Shiran Nanayakara for helping me for the control system design and implementation.

Further more I would like to express my great appreciation to all academic staff members of the Department of Electronics and Telecommunication Engineering and workshop staff for their kind support. Dissertations

Finally I would like to thank to all my fellow researchers of the Intelligent Machines Laboratory for their enormous support throughout this period.

W Rameesha De Silva

Department of Electronics and Telecommunication Engineering
University of Moratuwa

Contents

	Declaration	
	Abstract	
	Dedication	
	Acknowledgments	
	List of figures	
	List of tables	
1	Introduction University of Moratuwa, Sri Lanka.	-
	1.1 Motivation Electronic Theses & Dissertations	•
	1.2 The project goals land achievements	
	1.3 Organization of the thesis	
2	Preliminary investigations	2
	2.1 Literature Survey	
	2.1.1 Swedish wheel (omni wheel) designs	
	2.1.2 Power caster design	
	2.1.3 Other state of the art outdoor holonomic designs	
	2.1.4 Holonomic motion and non-holonomic motion	
3	Kinematics of the holonomic mobile platform	10
	3.1 Free body diagram of the mobile platform	
	3.2 Inverse hipometics relative	- · 11
	3.3 Possible webst meeting	14
Į	Modeling and simulation of mobile manipulators	15
	4.1 Mothersetical 1.1:	15

	4.2	2 Simulation						
	4.3	Newton Euler dynamics						
		4.3.1 Newton Euler formulation for manipulators						
		4.3.2 Newton Euler dynamics for mobile manipulators						
5	Me	chanical design of holonomic mobile platform	29					
	5.1	Wheels mount arms with drive system	29					
	5.2	Main body						
	5.3	3D model of the mobile platform						
	5.4	Mechanical power transmission system						
	5.5	Steering power transmission						
	5.6	Drive power transmission						
	5.7	Mechanical system implementation						
6	Mot	tion planning and controller design	35					
	6.1	Controller architecture of Moratuwa, Sri Lanka	35					
	6.2	Motion plandectronic Theses & Dissertations	35					
	6.3	Servo controllerw, lib. mrt. ac. lk	37					
	6.4	Control system timing and flow						
	6.5	Electronics and electrical system implementation	40					
7	Resi	ults and discussion	43					
	7.1	PID parameter tunning results	43					
	7.2	Holonomic robot in action	44					
8	Con	clusions and future research	47					
	8.1	Future works	47					
Bi	bliog	raphy	50					
Aj	ppenc	lix	50					
A	Mast	ter controller circuit	51					
В	Serv	o controller circuit	55					

List of Figures

2.1	Swedish wheel holonomic design	į
2.2	Typical omni wheel designs	
2.3	Power caster module used in XR4000 mobile Robot	(
2.4	Power caster holonomic design, XR4000 mobile Robot	,
2.5	Seekur holonomic robot	
2.6	Holonomic motion	
2.7	Non-holonomic motion University of Moratuwa, Sri Lanka.	ç
3.1	Free body Flactronic Theses & Dissertations	٠.
3.2	Kinematics digram of body section	12
3.3	Kinematics digram of single wheel	13
3.4	Kinematics digram of body section	14
3.5	Kinematics digram of body section	14
4.1	Simulation flow diagram	16
4.2	Osculating circles for given trajectory $y = f(x) \dots \dots$	20
4.3	$f(x) = (x/10)^3 - 8(x/10)^2 + x \qquad \dots $	21
4.4	$r(x)$ variation of $f(x) = (x/10)^3 - 8(x/10)^2 + x$	22
4.5	Virtual link concept	23
4.6	Simulated manipulator arm movements	26
4.7	Force applied on the mobile base when it is stationary	26
4.8	Force applied on the 121 1	27
4.9	Torques applied on the second	28
5.1	Wheel mount arm	30



5.2	Main body of mobile platform	31
5.3		32
5.4		
5.5		
6.1	Control system block diagram	36
6.2		
6.3		
6.4		
6.5		40
6.6	Dual servo card	41
6.7	Servo card stack	
6.8	PIC32 starter kit with I/O expansion	
6.9	Electrical wiring block diagram	
7.1	Step response Port 20 port Out of the Still 6 ms (Unstable)	43
7.2	P 10, D Electrore of Telesce ws (Settling times is high)	43
7.3	P = 10, D # 200, li = 10, Trs = 11.6 ms (Stable with an offset)	44
7.4	P = 10, $D = 200$, $I = 1$, $Ts = 1.6$ ms (Required step responce)	44
7.5	Holonomic type obstacle avoidance movement of the robot	45
7.6	Robot trajectory for the obstacle avoidance movement	46
7.7	Robot orientation error over the obstacle avoidance period	46
8.1	Proposed holonomic mobile manipulator system	48
A.1	Master controller	51
A.2	Master controller circuit diagram part 1	
A.3	Master controller circuit diamage 4	53
A.4	Master controller circuit dia mana a 1 2	54
B.1	Servo controller prototype	55
B.2	Serve controller gircuit dia	56
B.3	Servo controller circuit diagrams and a	57
B.4	Sorve controller singuit 1:	58

List of Tables

4.1	Simulation way points		•	•	 •			•		•		25
6.1	Ziegler-Nichols parameter tuning											39

